

Since 1976

KOCOM



KLP-C420/C420R



4Wire Common Gate Lobbyphone

KLP-C420 Series


- Stylish design with Touch button keypad
- Keypad Backlight on automatically at night
- Up to 450 Houses connection
- Easy to install only with 4 wires of BUS system
- Audio & Video Conversation with Visitor
- Door open Function by Access Code or by RF card(*KLP-C420R)
- White LED on to help a user to identify the visitor well at night
- Extension the same Lobbyphone up to 4 units
- Camera Angle adjustable

Compatible with all kocom 4wire monitor

Dual Application for both Single house and Multi-apartment with the same monitor

Original Version

System Diagram



* Number of extension units for each house is equivalent with the number when the main monitor is used with a door camera for a single house. For example, KCV-A374 supports up to 2 monitors and 2 sub audio phones.

Compatible Units

Monitor



KVR-A510 / D510
KCV-A510R




KCV-A374 / D374



KCV-301
(Color)

Lobbyphone KLP-C420 Series

Dimension (mm)



Specifications

Model No.	KLP-C420	KLP-C420R
Input Power	DC 15V±1V	
	Standby : Max. 2W Operation : Max. 6W	Standby : Max. 3W Operation : Max. 7W
Communication Method	KOCOM PROTOCOL DATA TX/RX Mode	
Speak Mode	Hands free type	
Timer	Call Duratin Time : 180 seconds (Call Waiting Time depends on a wall pad interlocked.)	
Housing Material	Aluminium (A/L), PC, ABS	
Dimension(mm)	174(W) x 263(H) x 15(D) / Box : 200(W) x 270(H) x 85(D)	
Operation Temperature	-20°C ~ +50°C	
LED Lighting Functions	10Key LED : It turns on when operating a key.	
	Mode-Lamp LED : It turns on below a certain illuminance.	
	Camera LED : It turns on when calling a house at a low minance.	
Angle of View	It controls an angle at a direction of up, down, right and left.	
RF Card Interlocking	N/A	13.56 MHz
Monitor Connection	KVM-301, KCV-301, KVM-340, KCV-340, KCV-A374/D374, KCV-A374SD/D374SD, KCV-A510R, KVR-A510/D510	
	Using Guard Station KAM-D340	Color Monitor : (4.3") KCV-434/D434, KCV-434SD/D434SD, KCV-454/D454, (7") KCV-504/D504, KCV-544 Doorphone : KDP-602GD

Repeater KVS-A4P / KVS-A8P

Dimension (mm)



Specifications

Model No.	KVS-A4P	KVS-A8P
Input Power	DC 13V±2	DC 13V±2V
	Operation : Max. 6W	Operation : Max. 7W
Wall Pad Connection	connect maximum 4EA (House 1 ~ House 4)	connect maximum 8EA (House 1 ~ House 8)
Data Mode	Lobby Phone and KOCOM Protocol Data TX/RX Mode	
Dimension(mm)	90(W) x 145(H) x 40(D)	
Operation Temperature	-10°C ~ +50°C	
LED Lighting Functions	Power LED : It checks the input state of the power.	
	Lobby LED : It checks the connection state of the lobby.	
	House LED : It checks the connection state of the house.	

KOCOM

KOCOM CO.,LTD.

Head Office KOCOM BLDG., 22, Arayuk-ro, Gochon-eup, Gimpo-si, Gyeonggi-do, 415-816, Korea

TEL : +82-2-6675-2211 | FAX : +82-2-6675-2000 | E-mail : export@kocom.com | www.kocom.com

※This catalog is based on the date as shown in the right and specifications are subject to change without notice for quality improvement.

P0402